

MAGX-000025-150000



GaN on SiC HEMT Power Transistor
150 W, 1-2500 MHz

Rev. V1

Features

- GaN on SiC Transistor Technology
- Broadband Unmatched Transistor
- Common-Source Configuration
- +50 V Typical Operation
- Class AB Operation
- RoHS* Compliant and 260°C Reflow Compatible
- MTTF = 600 years ($T_J < 200\text{ }^\circ\text{C}$)


Applications

- General purpose for pulsed or CW applications

Description

The MAGX-000025-150000 is a gold-metalized Gallium Nitride (GaN) on Silicon Carbide (SiC) RF power transistor suitable for a variety of RF power amplifier applications. Using state of the art wafer fabrication processes, these high performance transistors provide high gain, efficiency, bandwidth, and ruggedness over a wide bandwidth for today's demanding application needs. High breakdown voltages allow for reliable and stable operation under more extreme mismatch load conditions compared with older semiconductor technologies.


MAGX-000025-150000



Ordering Information

Part Number	Description
MAGX-000025-150000	Flanged
MAGX-000025-SB2PPR	1200-1400 MHz Evaluation Board
MAGX-000025-SB1PPR	2500 MHz Evaluation Board

Functional Schematic



* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

GaN on SiC HEMT Power Transistor 150 W, 1-2500 MHz

Rev. V1

Electrical Specifications¹: Freq. = 1200-1400 MHz, T_A = 25°C

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Units
RF Functional Tests: V_{DD} = 50 V, I_{DQ} = 600 mA, 300 μs Pulse, 20% Duty						
Output Power	P _{IN} = 2.5 W	P _{OUT}	150	170	-	W
Power Gain	P _{IN} = 2.5 W	G _P	17.5	18	-	dB
Drain Efficiency	P _{IN} = 2.5 W	η _D	52	58	-	%
Droop	P _{IN} = 2.5 W	Droop	-	0.2	0.3	dB
Load Mismatch Stability	P _{IN} = 2.5 W	VSWR-S	-	5:1	-	-
Load Mismatch Tolerance	P _{IN} = 2.5 W	VSWR-T	-	10:1	-	-

Typical RF Characteristics²: Freq. = 2500 MHz, T_A = 25°C

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Units
RF Functional Tests: V_{DD} = 50 V, I_{DQ} = 600 mA, 300 μs Pulse, 20% Duty						
Output Power	P _{IN} = 7 W	P _{OUT}	-	125	-	W
Power Gain	P _{IN} = 7 W	G _P	-	12.5	-	dB
Drain Efficiency	P _{IN} = 7 W	η _D	-	48	-	%
Droop	P _{IN} = 7 W	Droop	-	0.1	-	dB
Load Mismatch Stability	P _{IN} = 7 W	VSWR-S	-	5:1	-	-
Load Mismatch Tolerance	P _{IN} = 7 W	VSWR-T	-	10:1	-	-
RF Functional Tests: V_{DD} = 28 V, I_{DQ} = 600 mA, CW						
Input Power	P _{OUT} = 35 W	P _{IN}	-	2	-	W
Power Gain	P _{OUT} = 35 W	G _P	-	12	-	dB
Drain Efficiency	P _{OUT} = 35 W	η _D	-	45	-	%
Load Mismatch Stability	P _{OUT} = 35 W	VSWR-S	-	5:1	-	-
Load Mismatch Tolerance	P _{OUT} = 35 W	VSWR-T	-	10:1	-	-

Electrical Characteristics³: T_A = 25°C

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Units
DC Characteristics (Per Side):						
Drain-Source Leakage Current	V _{GS} = -8 V, V _{DS} = 175 V	I _{DS}	-	2	5.28	mA
Gate Threshold Voltage	V _{DS} = 5 V, I _D = 75 mA	V _{GS(TH)}	-5	-3.1	-2	V
Forward Transconductance	V _{DS} = 5 V, I _D = 17.5 mA	G _M	2	2.8	-	S
Dynamic Characteristics (Per Side):						
Input Capacitance	V _{DS} = 0 V, V _{GS} = -8 V, F = 1 MHz	C _{ISS}	-	26.4	-	pF
Output Capacitance	V _{DS} = 50 V, V _{GS} = -8 V, F = 1 MHz	C _{OSS}	-	11.2	-	pF
Reverse Transfer Capacitance	V _{DS} = 50 V, V _{GS} = -8 V, F = 1 MHz	C _{RSS}	-	1	-	pF

1. Electrical Specifications measured in MACOM RF evaluation board.

2. Typical RF Characteristics measured in MACOM RF evaluation board.

3. All DC Characteristics are per side.

2

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit www.macomtech.com for additional data sheets and product information.

GaN on SiC HEMT Power Transistor 150 W, 1-2500 MHz

Rev. V1

Absolute Maximum Ratings^{4,5,6,7,8}

Parameter	Limit
Supply Voltage (V_{DD})	+65 V
Supply Voltage (V_{GS})	-8 to -2 V
Supply Current ($I_{D_{MAX}}$) for CW operation at $V_{DD} = 28$ V	5.5 A
Supply Current ($I_{D_{MAX}}$) for pulsed operation at $V_{DD} = 50$ V	8.3 A
Input Power (P_{IN}) for CW operation at $V_{DD} = 28$ V	P_{IN} (typical) + 1.5 dB
Input Power (P_{IN}) for pulsed operation at $V_{DD} = 50$ V	40 dBm
Absolute Max. Junction/Channel Temperature	200°C
Power Dissipation at 85 °C for CW operation at $V_{DD} = 28$ V	79 W
Power Dissipation at 85 °C for pulsed operation at $V_{DD} = 50$ V	177 W
Thermal Resistance, ($T_J = 200$ °C) $V_{DD} = 28$ V, $I_{DQ} = 600$ mA, $P_{out} = 35$ W, CW	1.45 °C/W
Thermal Resistance, ($T_J = 200$ °C) $V_{DD} = 50$ V, $I_{DQ} = 600$ mA, $P_{in} = 7$ W, pulsed	0.65 °C/W
Operating Temperature	-40 to +95°C
Storage Temperature	-65 to +150°C
Mounting Temperature	See solder reflow profile
ESD Min. - Charged Device Model (CDM)	300 V
ESD Min. - Human Body Model (HBM)	700 V

4. Operation of this device above any one of these parameters may cause permanent damage.
5. For CW operation, Input Power limit is +1.5 dB over nominal drive required to achieve $P_{OUT} = 35$ W.
6. Channel temperature directly affects a device's MTTF. Channel temperature should be kept as low as possible to maximize lifetime.
7. For saturated performance it is recommended that the sum of $(3 \cdot V_{DD} + \text{abs}(V_{GG})) < 175$ V.
8. Pulsed operation is specified for a 300 μ s Pulse, 20% Duty.

Test Fixture Impedances (Per Side)

F (MHz)	Z _{IF(1,2)} (Ω)	Z _{OF(1,2)} (Ω)
1200	0.8 + j0.5	9.4 + j4.1
1300	0.9 + j0.2	7.2 + j3.0
1400	0.5 - j0.2	5.4 + j3.4
2500	1.2 - j3.4	3.1 + j1.4


Correct Device Sequencing

Turning the device ON

1. Set V_{GS} to the pinch-off (V_P), typically -5 V.
2. Turn on V_{DS} to nominal voltage:
 [(300 μ s, 20%) = 50 V; (2.5 GHz, CW) = 28 V].
3. Increase V_{GS} until the I_{DS} current is reached.
4. Apply RF power to desired level.

Turning the device OFF

1. Turn the RF power off.
2. Decrease V_{GS} down to V_P .
3. Decrease V_{DS} down to 0 V.
4. Turn off V_{GS} .




MAGX-00025-150000




GaN on SiC HEMT Power Transistor
150 W, 1-2500 MHz

Rev. V1

Test Fixture Assembly (1200-1400 MHz)



Test Fixture Assembly (2500 MHz)




Application Section


Typical Performance Curves

1200-1400 MHz, 300 μ s Pulse, 20% Duty, $V_{DD} = 50$ V, $I_{dq} = 600$ mA

Output Power Vs. Input Power




Drain Efficiency Vs. Output Power




2500 MHz, 300 μ s Pulse, 20% Duty, $V_{DD} = 50$ V, $I_{dq} = 600$ mA

Output Power Vs. Input Power




Drain Efficiency Vs. Output Power




2500 MHz, CW, $V_{DD} = 28$ V, $I_{dq} = 600$ mA

Output Power Vs. Input Power



Drain Efficiency Vs. Output Power



MAGX-000025-150000



GaN on SiC HEMT Power Transistor
150 W, 1-2500 MHz

Rev. V1

Outline Drawing MAGX-000025-150000

