

# PX2 Series Heavy Duty Pressure Transducers Product Nomenclature

For example, **PX2AN1XX150PABDX** defines a PX2 Series Heavy Duty Pressure Transducer, Packard Metripak 150, standard, electrical connector type, 1/4-18 NPT pressure port type, 150 psi pressure range, absolute pressure reference, regulated: 0.25 Vdc to 10.25 Vdc output transfer function.

PX2 Series	A Electrical Connector Type	N1 Pressure Port Type	XX <sup>7</sup>	150P Pressure Range			A Pressure Reference	BD Output Transfer Function
				bar	Pa	psi		
<b>PX2</b> Heavy Duty Pressure Transducer <sup>1</sup> 	<b>A</b> Delphi Metri-Pack 150, Standard (UL 94 HB) <sup>2</sup> (For UL 94 V-0 version, see order code <b>J</b> below.) <b>B</b> Micro M12 (IEC 61076-2) <b>C</b> DIN (EN 175301-803C) <b>D</b> Deutsch (DTM04-3P) <b>E</b> Cable harness, 1 meter cable length <sup>3</sup> <b>F</b> Cable harness, 2 meter cable length <sup>3</sup> <b>G</b> Cable harness, 3 meter cable length <sup>3,4</sup> <b>H</b> Cable harness, 5 meter cable length <sup>3,4</sup> <b>J</b> Delphi Metri-Pack 150 (UL 94 V-0) <sup>2</sup>	<b>F1</b> 7/16-20 UNF 1/4 in 45° Flare Female Schrader (SAE J512) <b>F2</b> 7/16-20 UNF 45° Flare Male (SAE J513) <b>F3</b> 7/16-20 UNF 37° Flare Male (SAE J514) <b>G1</b> G1/4 (ISO 1179-3) <b>G2</b> G1/8 (ISO 1179-3) <b>M1</b> M12 x 1.5 (ISO 6149-3) <b>N1</b> 1/4-18 NPT <b>N2</b> 1/8-27 NPT <b>S1</b> 9/16-18 UNF (SAE J1926-3) <b>S2</b> 7/16-20 UNF (SAE J1926-3)	<b>001B</b> 1 bar <b>100K</b> 100 kPa <b>015P</b> 15 psi <b>1.6B</b> 1.6 bar <b>160K</b> 160 kPa <b>030P</b> 30 psi <b>002B</b> 2 bar <b>250K</b> 250 kPa <b>050P</b> 50 psi <b>2.5B</b> 2.5 bar <b>400K</b> 400 kPa <b>100P</b> 100 psi <b>004B</b> 4 bar <b>600K</b> 600 kPa <b>150P</b> 150 psi <b>006B</b> 6 bar <b>001G</b> 1 MPa <b>200P</b> 200 psi <b>008B</b> 8 bar <b>1.6G</b> 1.6 MPa <b>250P</b> 250 psi <b>010B</b> 10 bar <b>2.5G</b> 2.5 MPa <b>300P</b> 300 psi <b>016B</b> 16 bar <b>004G</b> 4 MPa <b>500P</b> 500 psi <b>025B</b> 25 bar <b>4.6G</b> 4.6 MPa <b>600P</b> 600 psi <b>040B</b> 40 bar <b>006G</b> 6 MPa <b>667P</b> 667 psi <b>046B</b> 46 bar <b>007G</b> 7 MPa <b>750P</b> 750 psi <b>060B</b> 60 bar <b>01KP</b> 1000 psi <b>070B</b> 70 bar	<b>A</b> Absolute <b>S</b> Sealed gage <sup>5</sup> <b>G</b> Vented gage <sup>6</sup>	<b>AA</b> Ratiometric 5.0 V: 10 %Vs to 90 %Vs <b>AB</b> Ratiometric 5.0 V: 5 %Vs to 95 %Vs <b>AC</b> Ratiometric 3.3 V: 10 %Vs to 90 %Vs <b>AD</b> Ratiometric 3.3 V: 5 %Vs to 95 %Vs <b>BC</b> Regulated: 1 Vdc to 6 Vdc <b>BD</b> Regulated: 0.25 Vdc to 10.25 Vdc <b>BE</b> Regulated: 0.5 Vdc to 4.5 Vdc <b>BG</b> Regulated: 1 Vdc to 5 Vdc <b>CH</b> Current: 4 mA to 20 mA			

<sup>1</sup>Not all catalog listing combinations are available. Custom products are available. Please contact Honeywell.  
<sup>2</sup>Mating connectors available from Honeywell are 3685301 (1 m cable length) and 3685302 (3 m cable length).  
<sup>3</sup>Three-wire cable is required for ratiometric and regulated outputs; two-wire cable is required for current output.  
<sup>4</sup>Three meter and five meter cables are only available with Output Transfer Function CH = Current, 4 mA to 20 mA.  
<sup>5</sup>Sealed gage option only available in pressure ranges at or above 100 psi.  
<sup>6</sup>Vented gage option only available in pressure ranges between 100 psi and 667 psi (not available on cable harness configurations).  
<sup>7</sup>Reserved for future use.