



MK2PN-I-AC24

Part Number: Manufacturer/Brand: Product description Datasheets: RoHs Status Stock Condition Ship From Shipment Way

MK2PN-I-AC24

Hong Kong

Omron Automation & Safety RELAY GEN PURPOSE DPDT 10A 24V MK2PN-I-AC24.pdf

Lead free / RoHS Compliant 6551 pcs stock

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

MANUFACTURER Omnon Automation & Safety DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compiliant QUANTITY AVAILABLE 6551 pcs DATA SHEET ■ Mc2PNET-AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OF YOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VAC - Max SERLES MK RELASE TIME 20ms RELASE TIME General Purpose PACKAGING Bulk OTHER NAMES MK2PNIAC24 OPERATING TEMPERATURE 10°C ~ 40°C OPERATE TIME 20ms MOUTHING TYPE Socketable MOUTHING TYPE Socketable MOUTHING TYPE (MSL) 1 (Unlimited) MOITHING TYPE (MSL) Lead free / ROHS Compilant LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant LEAD FREE STATUS / ROHS STATUS General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT FATING (CURRENT) 10A CONTACT F		Specifications of MK2PN-I-AC24
DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 6551 pcs DATA SHEET MK2PH-FAC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PNIAC24 OPERATING TEMPERATURE 10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) LED Indicator, Mechanical Indicator EFEATURES LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL VOLTAGE 24VAC <th>PART NUMBER</th> <th>MK2PN-I-AC24</th>	PART NUMBER	MK2PN-I-AC24
Lead free / RoHS Compliant QUANTITY AVAILABLE 6551 pcs DATA SHEET DATA SHEET 1URN ON VOLTAGE (MAX) 19.2 VAC 1URN ONF VOLTAGE (MIN) 7.2 VAC 1URN ONF VOLTAGE (MIN) 1URN ON STYLE 1URN ON	MANUFACTURER	Omron Automation & Safety
QUANTITY AVAILABLE 6551 pcs DATA SHEET ★MCPN-I-AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERNINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING MK2PNIAC24 OPERATING TEMPERATURE 10°C ~ 40°C OPERATING TEMPERATURE 20ms MOUNTING TYPE Socketable MOUNTING TYPE Socketable MOUNTING TYPE Lead free / RoHS Compliant FEATURES LED Indicator, Mechanical Indicator LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES LED Indicator, Mechanical Indicator CONTACT RATING (QURRENT) 10A CONTACT RATING (QURRENT) 50 Viver (Ag) CONTACT FORM DPDT (2 Form C) COLL VOLTAGE 24VAC COLL VOLTAGE 80 Ohns	DESCRIPTION	RELAY GEN PURPOSE DPDT 10A 24V
DATA SHEFT MK2PN-T-AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING MK2PNIAC24 OPERATING TEMPERATURE 10°C ~ 40°C OPERATING TEMPERATURE 30ms MOUNTING TYPE Socketable MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES LED Indicator, Mechanical Indicator CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 10A CONTACT FORM DPDT (2 Form C) COLI VOLTAGE 24VAC COLI VOLTAGE 30 kms COLI TYPE Non Latching COLI TYPE Non Latching COLI TYPE Non Latching	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MX2PNIAC24 OPERATING TEMPERATURE 10°C ~ 40°C OPERATING TYPE Socketable MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT FORM DPDT (2 Form C) COLL VOLTAGE 24VAC COLL VOLTAGE 24VAC COLL TYPE Non Latching COLL TYPE Non Latching	QUANTITY AVAILABLE	6551 pcs
TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING WK2PNIAC24 OPERATING TEMPERATURE 0.00°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEED INdicator, Mechanical Indicator DETAILED DESCRIPTION CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT FORM CONTACT FOR	DATA SHEET	MK2PN-I-AC24.pdf
FIRMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE SERIES MK RELASE TIME SOMS RELAY TYPE General Purpose PACKAGING OTHER NAMES MKZPNIACZ4 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATE TIME MOUNTING TYPE SOCKEEABLE MOUNTING TYPE SOCKEEABLE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT FARMING (CURRENT) OPD (2 Form C) CONTACT FORM CONTACT FORM CONTACT FORM COLL TYPE NON Latching COLL TYPE ON LATCHING (SB OHM) SH PIN (Octal) AMA MARIA MA	TURN ON VOLTAGE (MAX)	19.2 VAC
SERIES MK RELEASE TIME 20ms RELAY TYPE 36eneral Purpose PACKAGING MKZPNIACZ4 OPERATING TEMPERATURE 10°C ~ 40°C OPERATING TEMPERATURE 20ms MOUNTING TYPE 36ekable MOISTURE SENSITIVITY LEVEL (MSL) 1(Unlimited) LEAD FREE STATUS / ROHS STATUS LED INdicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT MATERIAL SINCE	TURN OFF VOLTAGE (MIN)	7.2 VAC
SERIESMKRELEASE TIME20msRELAY TYPEGeneral PurposePACKAGINGBulkOTHER NAMESMKZPNIAC24OPERATING TEMPERATURE1.0°C ~ 40°COPERATE TIME20msMOUNTING TYPESocketableMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantFEATURESLED Indicator, Mechanical IndicatorDOTACT RATING (CURRENT)10ACONTACT RATING (CURRENT)10ACONTACT MATERIALSilver (Ag)CONTACT FORMDPDT (2 Form C)COLI VOLTAGE24VACCOIL YOLTAGE34VACCOIL TYPENon LatchingCOIL TYPE68 Ohms	TERMINATION STYLE	Plug In, 8 Pin (Octal)
RELEAS TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MKZPNIAC24 OPERATING TEMPERATURE 10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES LED Indicator, Mechanical Indicator DOTIACT RATING (CURRENT) 30 CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL YPE Non Latching COIL TYPE So Boms	SWITCHING VOLTAGE	250VAC, 250VDC - Max
RELAY TYPE PACKAGING PACKAGING BUIK OTHER NAMES MKZPNIACZ4 OPERATING TEMPERATURE OPERATE TIME DEFRATE TIME MOUNTING TYPE SOCKETABLE MOUNTING TYPE SOCKETABLE MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) DIA CONTACT MATERIAL CONTACT FORM DPDT (2 Form C) COLI YOLTAGE 24VAC COIL TYPE Non Latching COLI LESISTANCE BEBASE BEBASE BUIK BUIK AMAGE BUIK B	SERIES	MK
PACKAGING DTHER NAMES MK2PNIAC24 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATE TIME MOUNTING TYPE SOCKEABLE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) CONTACT PARTING CONTACT FORM OPDT (2 Form C) COIL YOLTAGE AVAC COIL TYPE OB Non. Latching 68 Ohms	RELEASE TIME	20ms
OTHER NAMES OPERATING TEMPERATURE OPERATE TIME OPERATE TIME OPERATE TIME OROSCHABLE MOUNTING TYPE SOCKEABLE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LED Indicator, Mechanical Indicator DETAILED DESCRIPTION CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT FORM ODDITION CONTACT FORM CONTACT FORM COLL VOLTAGE COLL VOLTAGE OLI LYPE OLI LYPE SONN SONN SONN SONN SONN SONN SONN SON	RELAY TYPE	General Purpose
OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS LEVEL (MSL) LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT FORM DPDT (2 Form C) CONTACT FORM DPDT (2 Form C) COLL VOLTAGE 24VAC COLL TYPE Non Latching 68 Ohms	PACKAGING	Bulk
OPERATE TIME 20ms MOUNTING TYPE 20cketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS LED Indicator, Mechanical Indicator DETAILED DESCRIPTION 20ceral Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COLL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms	OTHER NAMES	MK2PNIAC24
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT FORM CONTACT FORM DPDT (2 Form C) COLL VOLTAGE COLL VOLTAGE COLL YPE Non Latching 68 Ohms	OPERATING TEMPERATURE	-10°C ~ 40°C
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS FEATURES LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL CONTACT FORM DPDT (2 Form C) COIL VOLTAGE COIL VOLTAGE Non Latching COIL RESISTANCE 1 (Unlimited) LED Indicator, Mechanical Indicator General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable LED Indicator, Mechanical Indicator General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable DPDT (2 Form C) 24VAC Coil Socketable Silver (Ag) DPDT (2 Form C) AVAC COIL YPE Non Latching 68 Ohms	OPERATE TIME	20ms
LEAD FREE STATUS / ROHS STATUS FEATURES LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) DPDT (2 Form C) COIL VOLTAGE COIL VOLTAGE AVAC COIL TYPE Non Latching 68 Ohms	MOUNTING TYPE	Socketable
EEATURES LED Indicator, Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) DPDT (2 Form C) COIL YOLTAGE 24VAC COIL TYPE Non Latching 68 Ohms	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms	FEATURES	LED Indicator, Mechanical Indicator
CONTACT MATERIAL CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching 68 Ohms	DETAILED DESCRIPTION	General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable
CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms	CONTACT MATERIAL	Silver (Ag)
COIL TYPE Non Latching COIL RESISTANCE 68 Ohms	CONTACT FORM	DPDT (2 Form C)
COIL RESISTANCE 68 Ohms	COIL VOLTAGE	24VAC
	COIL TYPE	Non Latching
COIL POWER 2.3 VA	COIL RESISTANCE	68 Ohms
	COIL POWER	2.3 VA

Related Tags

Omron Automation & Safety MK2PN-I-AC24	MK2PN-I-AC24 Distributor	MK2PN-I-AC24 Supplier
MK2PN-I-AC24 Price	MK2PN-I-AC24 Pictures	MK2PN-I-AC24 Image
MK2PN-I-AC24 PDF Datasheet	MK2PN-I-AC24 Download Datasheet	MK2PN-I-AC24 Datasheet
MK2PN-I-AC24 Stock	Buy MK2PN-I-AC24	Buy Omron Automation & Safety MK2PN-I-AC24
Omron Automation & Safety MK2PN-I-AC24	Omron Automation & Safety Supplier	Omron Automation & Safety Distributor
Omron Automation & Safety MK2PN-I-AC24	Omron Automation and Safety MK2PN-I-AC24	

Related Products



Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 240V In stock: 3082 pcs

RFQ

MK2PN-I-AC120

MK2PN-I-AC240

OMRON

Description: RELAY GEN PURPOSE DPDT 10A 220V In stock: 6645 pcs

Manufacturers: Omron Automation & Safety

RFQ

MK2PN-I-DC6

MK2PN-I-AC220

ONRON AUTOMATION & SAFETY

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 120V In stock: 3813 pcs

RFQ

OMRON

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 6V In stock: 7082 pcs

RFQ

ONRON AUTOMATION & SAFETY

MK2PN-I-DC48 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 48V In stock: 3109 pcs

RFQ

OMRON

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 12V

MK2PN-I-AC12

In stock: 3695 pcs **RFQ**

MK2PN-I-DC110 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 110V In stock: 6662 pcs

RFQ

MK2PD-S-DC48 Manufacturers: Omron Automation & Safety

MK2PN-I-AC50

Description: RELAY GEN PURPOSE DPDT 10A 48V In stock: 4033 pcs

RFQ

ONRON AUTOMATION & SAFETY

MK2PN-I-AC110

MK2PD-S-DC12

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 110V In stock: 5353 pcs

RFQ

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 50V

In stock: 6193 pcs

RFQ



Description: RELAY GEN PURPOSE DPDT 10A 12V In stock: 5389 pcs

Manufacturers: Omron Automation & Safety

RFQ

Manufacturers: Omron Automation & Safety

MK2PN-I-DC24

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 6656 pcs

RFQ



Copyright © 2020 Reliable Distributor of Electronic Components











